

TES

Reliable in Quality

TES-137 Luminance Meter

- Dual Display, 4-digit LCD reading
- Measuring Levels Ranging 0.01 to 1999k cd/m², 0.001 to 580.0k fL
- Luminance ratio A/B, deviation %A, different B-A and peak luminance measurements
- User calibration factor and color-correction functions
- Accumulation luminance measurement
- Max/Min/AVG function
- Comparator function
- Data logger function
- USB Interface





Reliable in Quality

TES-137 Luminance Meter

FEATURES

- Dual Display, 4-digit LCD reading.
- Spectral Sensitivity close to CIE photopic Curve.
- Measuring Levels Ranging 0.01 to 1999k cd/m², 0.001 to 580.0k fL, Autoranging 6 step.
- Accurate and Instant response.
- Luminance ratio A/B, deviation %A, different B-A and peak luminance measurements.
- User calibration factor and color-correction functions.
- Accumulation luminance measurement.
- Max/Min/AVG function.
- Backlit function.
- Comparator function.
- Auto power off function.
- Data Hold function.
- Data memory and read function.
- Data logger function.
- USB Interface.

APPLICATIONS

- Luminance measurement of LCDs, CRTs, LEDs, etc.
- Luminance measurement of street lighting, tunnel lighting, etc.
- Measurement of airport lighting facilities.
- Transmittance measurement for LCD polarizing plates and various filters.
- Measurement of medical lighting.
- Illuminance irregularities of automobile license plates.
- Luminance measurement of various lighting facilities, etc.

SPECIFICATIONS

Display	Dual display 4 digit LCD read out.
Measuring Range	99.99, 999.9, 9999, 99.99k, 999.9k, 1999k cd/m ² 9.999, 99.99, 999.9, 9999, 99.99k, 580.0k fL Auto ranging (6 step) (1 fL = 3.426 cd/m ²)
Measuring Angle	2°
Overrange Display	OL is displayed
Resolution	0.01 cd/m ² , 0.001 fL
Accuracy	±3% rdg ±5dgt (Calibrated to standard incandescent lamp, 2856°K, at 25°C / 77 °F)
CIE Photopic f _v	≤ 6%
Temperature Characteristics	±0.1%/ °C
Measuring Rate	Approximately 5 time/sec
Photosensor	Silicon photodiodes
Data Memory Capacity	999 sets. (Direct reading from LCD display)
Data Logger Capacity	microSD CARD 4GB
Operating / Storage Conditions	0°C to 50°C <80% RH -10°C to 60°C <70%RH
Power Source	6 pcs AAA size Battery
Battery Life (typical)	100 hours
Photosensor Lead Length	150 cm (approx.)
Photosensor Dimensions	40φ×158(L)mm
Dimension	150(L) × 72(W) × 35(H)mm
Weight	Meter: 235g, Photosensor: 210g
Accessories	Carrying case, Instruction manual, Battery, CD software, USB cable.



TES ELECTRICAL ELECTRONIC CORP.

7F, No.31 Lane 513, Rui Guang Rd., Neihu Dist, Taipei, Taiwan

Tel : (02) 2799-3660 Fax : 886-2-2799-5099

E-mail : tes@ms9.hinet.net

<http://www.tes.com.tw>