THE PROPERTY OF THE PROPERTY O

RK2674C Hi-pot tester

제품특징

RK2674C Withstand voltage tester

Product introduction

The RK2674C Withstand voltage tester of Meiruike is the measurement instrument for compressive strength, it mainly used for insulation leakage safety test of product. It can test the electrical safety performance index of breakdown voltage, leakage current of which all kind of the measured object intuitive, accurate and fast, and can be used for testing the components and overall performance as a high voltage source.

This series of tester according to the following standards:Standard for household electrical appliances(IEC6035,GB4706.1-2001, GB4706.1-1998),Standard for lamp(IEC60598-1-1999, GB7000.1-2000),Standard for information (GB8898-2001,GB12113.GB4943-2001, IEC60065,IEC60950) and so on.

Application area

Components:diode,triode,high-voltage silicon stack,all kinds of electronic transformer, connector assembly,high voltage electrical equipment.

Household Electric Appliances:TV,refrigerator,air conditioner,washing machine,dryer, electric blanket,charger etc.

Insulation material:heat shrinkable tube,capacitor film,high pressure tube,insulating paper,insulated shoes,rubber insulating gloves,PCB circuit board etc.

Instruments and meters:oscilloscope, signal generator, DC power supply, switching power supply and other types of machine.

Lighting appliances:ballast,road lights,stage lights,portable lamps and other types of lamps.

Electric heating appliances:electric drill,pistol drill,cutting machine,grinding machine,electric welding machine etc.

Wire and cable:high voltage cable,optical cable,electric cable,silicone rubber cable, etc.

Performance characteristics

The output voltage regulated output by the regulator, which has high reliability and high durability.

Using high brightness LED digital displaying test time, voltage, current, it can display the breakdown current value and voltage value in real time.

Test time using three digital tube display

제품사양

Model		RK2674A	RK2674C
Output Voltage (I	AC <v)<="" td=""><td>0~20</td><td>0~50</td></v>	0~20	0~50
	DC	0~20	0~50
Output Cui	r eAo E (mA)	0~2/20	0~2/20/40
	DC	0~2/10	0~2/20
Test accuracy		±5%	
Test time		(0.0~999)s 0.0=continuous test	1-99s ±1%
Transformer capacity		400VA	2000VA
Interface of PLC		optional	No
Power Requirments		AC:220V±10% 50Hz/60Hz	
Working environment		Temperature:(0-40)°C Humidity≤75%RH	
Exterior style		Desktop type	Separate type
Exterior dimension		450×515×230	(1)370×300×200
			(2)850×480×720
Weight		35kg	(1)11.5kg (2)65kg
Accessory		High voltage test line,ground wire,power line	High voltage test line,ground wire,power line,high voltage discharge stick,connecting line