



Moisture Meters Ltd, Westgate, Bradford, BD1 3SQ. Tel ++44(0)1274 733582, Fax: ++44(0)1274 370151, e-mail: mail@shawmeters.com, URL: www.shawmeters.com



## SU4 Specification.

Sensor inserted for illustration purposes.

### Description

Sample Conditioning Unit, for wall mounting, comprising pressure regulator, flow indicator, and sensor holder mounted on a stove enamelled backplate.

Conditions flow of sample gas to the required 2-10 litres per minute at near atmospheric pressure for accurate and consistent sampling.

Pneumatic connections with a choice of 1/8", 1/4" or 6mm compression fittings if required for inlet and outlet.

4 x 5mm mounting holes at 240 x 140mm (H x W rectangle).

### Dimensions / Weight:

Overall dimensions: 260mm x 160mm x 135mm depth. Weight: 1.6-1.8Kg approx.

### Sampling Options:

Input Pressure (pr): Upto 28Bar (Lo), 200Bar (Med), 400 Bar (Hi).

### Options:

Filter Unit.(for 28 and 200Bar variants only)

Firtree fittings for 6mm i.d. hose (low pressure only typically <8Bar)

### To Order:

SU4-Lo (1/8", 1/4" or 6mm fittings) for 28 Bar variant

SU4-Me (1/8", 1/4" or 6mm fittings) for 200 Bar variant

SU4-Hi (1/8", 1/4" or 6mm fittings) for 400 Bar variant

(Please state required fittings with order)